



ACTIVE GEOANCHOR INC.
SLOPE PROTECTION WORKS + GROUND IMPROVEMENT
 active1998@gmail.com + activegeoanchor@gmail.com

FIELD BORING LOG

Project: PROPOSED PGH BUILDING (SITE 2)							Boring No.: BH-1											
Location: OETS, TAFT AVENUE, ERMITA, MANILA							Total Depth: 42 M											
Hole Logged by: RONALD LIM					Name of Driller: JIMSON DEL ROSARIO													
Sampling Method: SPT					Type of Drilling: CONCORE													
Hammer Wt: 140 LBS					Height of Drop: 76 CM													
Date Started: OCT 06, 2018			Time: 01:10 PM		Date Finished: OCT 10, 2018		Time: 11:30 AM											
S A M P L E R D E P T H	S A M P L E R T Y P E	B L O W S	D R I V E N	R E C O V E R Y	N V A L U E	% R Q D	D E P T H I N F T / M	Boring Depth:	42 M									
								Casing Depth:	12 M									
								Water Depth:	3.35 M									
								Date:	OCT 11, 2018									
								Time:	11:30 AM									
								Surface Elevation										
								DESCRIPTION OF MATERIALS										
								0.55 1.00	SPT 1	2-2-3	45	42	5		Brown Sandy Silt			
								1.55 2.00	SPT 2	4-7-9	45	40	16		Brown Sandy Silt			
								2.55 3.00	SPT 3	2-3-2	45	20	5		Gray Sandy Silt			
3.55 4.00	SPT 4	4-3-3	45	44	6		Gray to Brown Sandy Silt											
4.55 5.00	SPT 5	3-2-2	45	45	4		Brown Sandy Silt											
5.55 6.00	SPT 6	1-1-1	45	44	2		Gray Sandy Silt											

FIELD BORING LOG

DEPTH	TYPE	BLOWS	DRIVEN	RECOVERY	N VALUE	% RQD	DEPTH	Project:	PROPOSED PGH BUILDING (SITE 2)
								Location:	OETS, TAFT AVENUE, ERMITA, MANILA
								Boring No.:	BH - 1
								DESCRIPTION OF MATERIALS	
7.05 7.50	SPT 7	Hammer Weight	45	44	HW				Gray Silty Clay
8.55 9.00	SPT 8	1/45	45	40	1				Gray Silty Clay
10.05 10.50	SPT 9	3-1-2	45	41	3				Gray Silty Clay with Shells
11.55 12.00	SPT 10	3-4-2	45	18	6				Gray Sandy Silt
13.05 13.50	SPT 11	9-8-9	45	42	17				Gray Silty Clay
14.55 15.00	SPT 12	7-9-11	45	43	20				Brown Sandy Silt
16.05 16.50	SPT 13	11-9-12	45	39	21				Brown Sandy Silt
17.55 18.00	SPT 14	6-6-9	45	45	15				Brown Sandy Silt
19.05 19.50	SPT 15	10-8-10	45	43	18				Brown Sandy Clay
20.55 21.00	SPT 16	7-11-15	45	43	26				Brown Sandy Clay



ACTIVE GEOANCHOR INC.
SLOPE PROTECTION WORKS • GROUND IMPROVEMENT
active1996@gmail.com + activegeoanchor@gmail.com

FIELD BORING LOG

D E P T H	T Y P E	B L O W S	D R I V E	R E C O V E	N V A L	% R Q D	D E P T H	Project: PROPOSED PGH BUILDING (SITE 2)	
								Location: OETS, TAFT AVENUE, ERMITA, MANILA	
								Boring No.: BH - 1	
								DESCRIPTION OF MATERIALS	
22.05 22.50	SPT 17	15-16-14	45	40	30			Light Brown Silty Clay	
23.55 24.00	SPT 18	11-8-10	45	45	18			Gray Silty Clay	
25.05 25.50	SPT 19	7-9-10	45	43	19			Gray to Brown Silty Clay	
26.55 27.00	SPT 20	5-6-7	45	42	13			Gray Silty Clay	
28.05 28.50	SPT 21	7-7-9	45	40	16			Gray Silty Clay	
29.55 30.00	SPT 22	8-9-11	45	41	20			Gray Silty Clay	
31.05 31.50	SPT 23	7-12-16	45	43	28			Gray Silty Clay	
32.55 33.00	SPT 24	12-18-21	45	40	39			Gray Sandy Clay	
34.05 34.50	SPT 25	14-17-19	45	43	36			Gray Silty Clay	
35.55 36.00	SPT 26	16-16-21	45	40	37			Gray Silty Clay	



ACTIVE GEOANCHOR INC.
SLOPE PROTECTION WORKS + GROUND IMPROVEMENT
 active1998@gmail.com + activegeoanchor@gmail.com

FIELD BORING LOG

Project: PROPOSED PGH BUILDING (SITE 2)							Boring No.: BH-2											
Location: OETS, TAFT AVENUE, ERMITA, MANILA							Total Depth: 30 M											
Hole Logged by: RONALD LIM					Name of Driller: JIMSON DEL ROSARIO													
Sampling Method: SPT					Type of Drilling: CONCORE													
Hammer Wt: 140 LBS					Height of Drop: 76 CM													
Date Started: OCT 10, 2018			Time: 04:20 PM		Date Finished: OCT 13, 2018		Time: 11:40 AM											
S A M P L E R D E P T H	S A M P L E R T Y P E	B L O W S	D R I V E N	R E C O V E R Y	N V A L U E	% R Q D	D E P T H I N F T / M	Boring Depth:	30 M									
								Casing Depth:	12.70 M									
								Water Depth:	1.20 M									
								Date:	OCT 14, 2018									
								Time:	01:00 PM									
								Surface Elevation										
								DESCRIPTION OF MATERIALS										
								0.55 1.00	SPT 1	4-3-3	45	40	6		Gray Silty Clay			
								1.55 2.00	SPT 2	5-5-6	45	41	11		Gray Silty Clay			
								2.55 3.00	SPT 3	4-3-3	45	40	6		Gray Sandy Clay			
3.55 4.00	SPT 4	3-2-3	45	42	5		Gray Sandy Clay											
4.55 5.00	SPT 5	2-1-2	45	32	3		Gray Sandy Silt											
5.55 6.00	SPT 6	2/45	45	40	2		Gray Sandy Silt											

FIELD BORING LOG

DEPTH	TYPE	BLOWS	DRIVEN	RECOVERY	N VALUE	% RQD	DEPTH	Project:	PROPOSED PGH BUILDING (SITE 2)
								Location:	OETS, TAFT AVENUE, ERMITA, MANILA
								Boring No.:	BH - 2
								DESCRIPTION OF MATERIALS	
7.05 7.50	SPT 7	1/45	45	39	1			Gray Sandy Clay	
8.55 9.00	SPT 8	Hammer Weight	45	35	HW			Gray Sandy Clay	
10.05 10.50	SPT 9	2-2-2	45	43	4			Gray Sandy Silt with shells	
11.55 12.00	SPT 10	3-1-2	45	43	3			Gray Clayey Silt with shells	
13.05 13.50	SPT 11	8-8-7	45	40	15			Brown Silty Clay	
14.55 15.00	SPT 12	3-3-4	45	38	7			Brown Clayey Silt	
16.05 16.50	SPT 13	8-7-8	45	42	15			Brown Clayey Silt	
17.55 18.00	SPT 14	6-9-10	45	37	19			Brown Silty Clay	
19.05 19.50	SPT 15	8-11-14	45	44	25			Brown Silty Clay	
20.55 21.00	SPT 16	8-11-12	45	41	23			Brown Silty Clay	



ACTIVE GEOANCHOR INC.
SLOPE PROTECTION WORKS + GROUND IMPROVEMENT
 active1998@gmail.com + activegeoanchor@gmail.com

FIELD BORING LOG

Project: PROPOSED PGH BUILDING (SITE 2)							Boring No.: BH-3											
Location: OETS, TAFT AVENUE, ERMITA, MANILA							Total Depth: 43.5 M											
Hole Logged by: RONALD LIM					Name of Driller: JIMSON DEL ROSARIO													
Sampling Method: SPT					Type of Drilling: CONCORE													
Hammer Wt: 140 LBS					Height of Drop: 76 CM													
Date Started: OCT 13, 2018			Time: 03:55 PM		Date Finished: OCT 16, 2018		Time: 05:20 PM											
S A M P L E R D E P T H	S A M P L E R T Y P E	B L O W S	D R I V E N	R E C O V E R Y	N V A L U E	% R Q D	D E P T H I N F T / M	Boring Depth:	43.5 M									
								Casing Depth:	14.20 M									
								Water Depth:	2.20 M									
								Date:	OCT 17, 2018									
								Time:	05:00 PM									
								Surface Elevation										
								DESCRIPTION OF MATERIALS										
								0.55 1.00	SPT 1	3-4-4	45	30	8	Brown Sandy Clay				
								1.55 2.00	SPT 2	4-5-4	45	43	9	Gray Sandy Silt				
								2.55 3.00	SPT 3	4-5-3	45	41	8	Gray Sandy Silt				
3.55 4.00	SPT 4	6-7-5	45	42	12	Gray Sandy Silt												
4.55 5.00	SPT 5	2-1-1	45	43	2	Gray Sandy Silt with shells												
5.55 6.00	SPT 6	1-1-1	45	44	2	Gray Sandy Silt with shells												

FIELD BORING LOG

DEPTH	TYPE	BLOWS	DRIVEN	RECOVERY	N VALUE	% RQD	DEPTH	Project:	PROPOSED PGH BUILDING (SITE 2)
								Location:	OETS, TAFT AVENUE, ERMITA, MANILA
								Boring No.:	BH - 3
								DESCRIPTION OF MATERIALS	
7.05 7.50	SPT 7	Hammer Weight	45	45	HW				
								Gray Sandy Silt with shells	
8.55 9.00	SPT 8	1/45	45	42	1				
								Gray Sandy Silt with shells	
10.05 10.50	SPT 9	2-2-2	45	40	4				
								Gray Sandy Silt with shells	
11.55 12.00	SPT 10	4-5-5	45	30	10				
								Gray Silty Clay	
13.05 13.50	SPT 11	7-7-9	45	26	16				
								Gray Silty Clay	
14.55 15.00	SPT 12	7-8-12	45	38	20				
								Brown Silty Clay	
16.05 16.50	SPT 13	8-11-12	45	40	23				
								Brown Silty Clay	
17.55 18.00	SPT 14	10-10-13	45	41	23				
								Brown Silty Clay	
19.05 19.50	SPT 15	9-9-10	45	43	19				
								Light Brown Clayey Silt	
20.55 21.00	SPT 16	9-11-11	45	37	22				
								Light Brown Clayey Silt	



ACTIVE GEOANCHOR INC.
SLOPE PROTECTION WORKS • GROUND IMPROVEMENT
active1996@gmail.com + activegeoanchor@gmail.com

FIELD BORING LOG

D E P T H	T Y P E	B L O W S	D R I V E	R E C O V E	N V A L	% R Q D	D E P T H	Project: PROPOSED PGH BUILDING (SITE 2)	
								Location: OETS, TAFT AVENUE, ERMITA, MANILA	
								Boring No.: BH - 3	
								DESCRIPTION OF MATERIALS	
22.05 22.50	SPT 17	11-12-15	45	45	27			Light Brown Silty Clay	
23.55 24.00	SPT 18	12-16-17	45	45	33			Brown to Gray Silty Clay	
25.05 25.50	SPT 19	16-15-29	45	43	34			Gray Silty Clay	
26.55 27.00	SPT 20	14-15-18	45	40	33			Gray Silty Clay	
28.05 28.50	SPT 21	11-16-16	45	44	32			Gray Silty Clay	
29.55 30.00	SPT 22	11-12-11	45	43	23			Gray Silty Clay with shells	
31.05 31.50	SPT 23	11-11-10	45	45	21			Gray Silty Clay with shells	
32.55 33.00	SPT 24	10-10-9	45	42	19			Gray Silty Clay with shells	
34.05 34.50	SPT 25	13-19-21	45	44	40			Gray Silty Clay	
35.55 36.00	SPT 26	14-16-18	45	38	34			Gray Silty Clay	

